

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 07-277923

(43)Date of publication of application : 24.10.1995

(51)Int.Cl.

A61K 7/02
A61K 7/00
A61K 7/027
C08L 83/12

(21)Application number : 06-087327

(71)Applicant : KANEBO LTD

(22)Date of filing : 01.04.1994


(72)Inventor : AOYANAGI SHIGERU
KOBAYASHI ICHIRO

(54) OILY COSMETIC

(57)Abstract:

PURPOSE: To obtain an oily cosmetic, capable of improving the adhesion unique thereto and reducing the stickiness and excellent in persistence of makeup effects.

CONSTITUTION: This oily cosmetic is obtained by blending (A) a polyether- modified silicone which is a linear copolymer containing a polysiloxane- polyoxyalkylene block expressed by the formula [R1 to R4 are each a 1-32C alkyl; (x) and (y) are each 1-8; (a) and (b) are each an integer providing the polyoxyalkylene with 300-10000 average molecular weight and a number providing 10-90wt.% polyoxyalkylene in the molecule; (m) is an integer providing the polysiloxane block with 400-10000 average molecular weight; (n) is ≥ 4 ; the linear block copolymer has at least 3000 average molecular weight] as a recurring unit with (B) a liquid polar oil comprising one or more compounds selected from the group of esters of ≥ 18 C monohydric alcohols, ≥ 3 C monohydric alcohols or cholesterol with ≥ 8 C fatty acids and esters of compounds having at least ≥ 2 hydroxyl groups with ≥ 7 C fatty acids. The amounts of the blended ingredients are 1.0-50.0wt.% ingredient (A) and 3.0-50.0wt.% ingredients (B).



LEGAL STATUS

[Date of request for examination] 28.09.1999

[Date of sending the examiner's decision of rejection] 01.07.2003

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision
of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office